

# Double Reel Trailer – Self Loading (MRT-D16-SL)

## Product Information

### Standard Features

Body Length	19 ft
Width	96 in
Height	88 in
Gross Vehicle Weight Rating (GVWR)	17,600 lbs*
Payload	13,500 lbs
Maximum Spool Diameter	120 in
Coupler Type	Adjustable Lunette Eye/Pintle (Standard) or 2-5/16 in Adjustable Ball Coupler. 16 in x 7 in Plate Mount with 4 ½ in bolt centers. Accommodates three adjustable heights. (Standard) <i>Option: 5-Position Adjustable Channel Coupler Mount</i>
Brakes	Electric, FSA (Fwd Self Adj) On all Axles
Tires & Wheels	235/80R16 LRG, 8 Bolt [16x6] MOD
Hydraulic Pump	Double-Acting 12V DC Hydraulic Pump Power Unit with Corded Control
Hydraulic Cylinders	30 in Stroke, 2.5 in Bore and 1.5 in Rod Diameter (2x)
Axles	8k (2x)
Axles Lubed	Oil Bath
Jack Type	12k Ram Jack - Bolt-On
Plug	7 Pole RV
Tail Lights	(4x) 6 in LED Oval Tail Lights
Marker Lights	(7x) Red 3/4 in, (4x) Amber 3/4 in
Trailer Color	White (Standard); <i>Black or Custom Color Options</i>

\*Trailer rating is calculated based on the proper load placement and weight displacement/transfer to the towing vehicle.



**Haul with the Best** / Learn more at [millertrailersmn.com](http://millertrailersmn.com)

Listed weight ratings, weights, and dimensions are for reference only. Miller Trailers reserves the right to change the materials or specifications at any time without prior notice. See our website or your local authorized dealer for more information.

©2024 Miller Trailers 01/2024